DUX-12F 4K HDMI OUTPUT BOARD



DUX-F-O-HDMI

The DUX-F-O-HDMI is a 4K and UHD (Ultra High Definition) capable and HDCP 2.2 compliant HDMI output board for the DUX-12F Switching Matrix Enclosure. It has three connections and supports HDMI with de-embedded audio.

FEATURES

- Supports up to 4K@60 4:4:4 8bit.
- HDCP 2.2 compliant.
- Balanced digital and analog audio de-embedding.

PACKING LIST

- 1 x DUX-F-O-HDMI
- 1 x 5-pin Pheonix connector

SPECIFICATIONS

General	
Compatible AMX products	Must be used in conjunction with a DUX-12F Switching Matrix Enclosure
Technical	
Connections	• 1 x HDMI OUT • 1 x Digital AUDIO OUT (S/PDIF Port) • 1 x Analog AUDIO OUT (5-pin Phoenix Female Port)
Video Type	HDMI with HDCP 2.2
Resolution Supported	• VESA: 1024 x 768[8], 1280 x 800[8], 1920 x 1200[8], 3840 x 2160[5,8] and Auto Scaler • SMPTE: 1280 x 720[8], 1920 x 1080[8] 1 = @ 23.98 Hz, 2 = @ 24 Hz, 3 = @ 25 Hz, 4 = @ 29.97 Hz, 5 = @ 30 Hz, 6 = @ 50 Hz, 7 = @ 59.94 Hz, 8 = @ 60Hz
Video Data Rate (Max)	18 Gbps
Video Level	0.5~1.2 Vp-p
DDC Signal	5 Vp-p
Maximum Pixel Clock	600 MHz
Audio Format	• HDMI OUT: PCM 2.0, Dolby 2.0, Dolby 5.1. • Digital AUDIO OUT: PCM 2.0, Dolby 2.0, Dolby 5.1. • Analog AUDIO OUT: PCM 2.0.
Physical	
Net Weight	0.22 kg

© 2022 Harman. All rights reserved. ENZO, NetLinx, AMX, AV FOR AN IT WORLD, HARMAN, and their respective logos are registered trademarks of HARMAN. Oracle, Java and any other company or brand name referenced may be trademarks/registered trademarks of their respective companies.

AMX does not assume responsibility for errors or omissions. AMX also reserves the right to alter specifications without prior notice at any time.

The AMX Warranty and Return Policy and related documents can be viewed/downloaded at www.amx.com.

3000 RESEARCH DRIVE, RICHARDSON, TX 75082

AMX.com | 800.222.0193 | 469.624.8000 | +1.469.624.7400 | fax 469.624.7153

08.2022

DUX-12F 4K HDMI 输出板卡



DUX-F-O-HDMI

DUX-F-O-HDMI 为 HDMI 输出板卡，支持 4K 超高清信号，兼容 HDCP 2.2，用于搭配 DUX-12F 切换矩阵使用。该输出板卡提供 3 个接口，支持 HDMI 音频解嵌。

产品特性

- 支持分辨率最高可达 4K@60 4:4:4 8bit；
- 兼容 HDCP 2.2；
- 支持平衡模拟与数字音频解嵌。

包装清单

- 1 x DUX-F-O-HDMI
- 1 x 5-针式凤凰接头

规格参数

常规	
兼容 AMX 产品	必须搭配 DUX-12F 切换矩阵使用
性能	
接口	• 1 x HDMI 输出 • 1 x 数字音频输出（S/PDIF接口） • 1 x 模拟音频输出（5-针式凤凰端子，母头）
视频类型	HDMI 兼容 HDCP 2.2
支持分辨率	• VESA: 1024 x 768[8]、1280 x 800[8]、1920 x 1200[8]、3840 x 2160[5,8]与自动缩放 • SMPTE: 1280 x 720[8]、1920 x 1080[8] 1 = @ 23.98 Hz、2 = @ 24 Hz、3 = @ 25 Hz、4 = @ 29.97 Hz、 5 = @ 30 Hz、6 = @ 50 Hz、7 = @ 59.94 Hz、8 = @ 60Hz
视频带宽（最大）	18 Gbps
视频等级	0.5~1.2 Vp-p
DDC 信号	5 Vp-p
最大像素时钟	600 MHz
音频格式	• HDMI 输出：PCM 2.0、Dolby 2.0、Dolby 5.1； • 数字音频输出：PCM 2.0、Dolby 2.0、Dolby 5.1； • 模拟音频输出：PCM 2.0。
外观	
净重	0.22 kg

© 2022 哈曼（HARMAN）。版权所有。ENZO、NetLinx、AMX、AV FOR AN IT WORLD、HARMAN以及相关标识均为哈曼（HARMAN）注册商标。Oracle、Java以及其它企业或品牌名称等可为相关注册商标。
AMX对文件中可能存在的信息错误或删减不承担法律责任。AMX保留更改规格的权利，恕不另行通知。
有关AMX质保与退货的相关文件，请访问www.amx.com。
3000 RESEARCH DRIVE, RICHARDSON, TX 75082
AMX.com | 800.222.0193 | 469.624.8000 | +1.469.624.7400 | fax 469.624.7153

08.2022