



GALLERY



Exterior Wash 110

Exterior™ Wash 110 is a powerful, compact and energy-efficient LED lighting fixture designed to illuminate smaller structures, features of a building and landscaping. A discreet, optional snoot integrates seamlessly with the slick design of the fixtures. It has built-in display for ease-of-use, a wide selection of beam angles and is fully IP-rated for permanent outdoor use.

The Exterior Wash 110 is designed for superior color mixing applications and is based on quad-color premixed LEDs.

Uniform color mixing with 6 beam angle options

Functional and discreet optional snoot which integrates with the design of the fixtures

Control via DMX, RDM and OLED display

FEATURES

- Powerful Premixed LEDs
- Up to 1300 lumens at full white (RGBW)
- Six different beam angle options
- Internal power and control (DMX, RDM and OLED display)
- Rugged IP66 housing
- 0–100% intensity control

TECHNICAL SPECIFICATIONS

Physical

Length: 240 mm (9.5 in.)
Width: 198 mm (7.8 in.)
Height: 257 mm (10.2 in.)
Weight: 5.0 kg (11.1 lbs.)

Dynamic Effects

Intensity: 0 - 100%
Color mixing: RGBW

Control and Programming

Control systems: DMX, RDM
DMX channels: 4
Setting, addressing, standalone programming: Control panel with OLED display
Receiver: RS-485
Firmware update: Serial upload via DMX link
DMX compliance: USITT DMX512-A
RDM compliance: ANSI/ESTA E1.20

Optics

Minimum LED lifetime: 50 000 hours (to >70% luminous output)*
Light source: 4 x RGBW quad-color LEDs
LED manufacturer: Cree

Beam angle options

No diffuser: 11°
Narrow diffuser: 16°
Medium diffuser: 24°
Wide diffuser: 52°
Very wide diffuser: 60°
Asymmetric diffuser: 54° x 16°

**Figure obtained under manufacturer's test conditions:*

Photometric Data

Total luminous output: 1300 lumens

Construction

Ingress protection rating: IP66
Surface treatment: Anodized and electrostatic powder-coated
Color: Light grey (white, black or other colors available on request)
Housing: Cast aluminum
Effective Projected Area (EPA): 0.05 m² including snoot
Impact resistance: IK08 (with control panel display cover plate installed)
Corrosion resistance: C5-M (very high corrosivity / marine, ISO 12944)
RoHS compliant

Installation
Orientation: Any
Mounting: Adjustable yoke
Vertical aiming: TBA
Minimum distance to illuminated surfaces: 0.2 m (0.6 ft.)

Connections
Power connection: 1.8 m (5.9 ft.) cable tail without connector
Power input cable type, EU models: H05RN-F 300/500V, 3 x 0.75 mm², Ø 7 mm
Power input cable type, US models: SJOW 18AWG, 300V, WL F1, Ø 8 mm
Data connection: 1.8 m (5.9 ft.) open ended 5-conductor combined input + output cable tail
All cable entries: IP68 cable gland

Electrical
AC power: 100 - 240 / 277 V nominal, 50/60 Hz
Power supply unit: Integrated, auto-sensing multi-voltage
Power consumption, steady state, all LEDs at zero intensity: 5 W
Maximum total power consumption: 50 W
Typical half-cycle RMS inrush current: 9.7 A
Surge protection: 4 KV

Typical Power and Current
100 V, 60 Hz: 0.45 A, 42 W, PF 0.99
120 V, 60 Hz: 0.35 A, 42 W, PF 0.99
230 V, 50 Hz: 0.2 A, 42 W, PF 0.96
277 V, 60 Hz: 0.2 A, 42 W, PF 0.90
Measurements made with fixture in steady state at nominal voltage, ambient temperature (Ta) 20° C (68° F), all LEDs at full intensity. Allow for a deviation of +/- 10%.

Thermal
Cooling: Convection
Maximum ambient temperature (Ta max.): 45° C (113° F)
Minimum ambient temperature (Ta min.): -30° C (-22° F), power must be maintained below -20° C (-4° F)
Maximum surface temperature, steady state, at 40° C ambient: 70° C (158° F)
Total heat dissipation (calculated, +/- 10%): 160 BTU/hr

Approvals
EU safety: EN60598-2-5 (EN60598-1), EN62471, EN62493, EN60598-2-1
EU EMC: EN55015, EN61547, EN61000-3-2, EN6100-3-3, EN61000-4-2, EN6100-4-4, EN6100-4-5
US safety: ANSI/UL 1598
US EMC: 47 CFR Part 15 Class A
Canadian safety: CSA C.22.2 No. 250
Australia/NZ: RCM

Included Items
Power cable: Cable tail, 1.8 m (5.9 ft.), external diameter 9.5 mm (0.38 in.), installed
Data cable: Cable tail, 1.8 m (5.9 ft.), external diameter 6.5 mm (0.26 in.), installed
Cover plate for control panel

Accessories

Optical:
Exterior Wash 100 Series, narrow diffuser kit: P/N 91610145
Exterior Wash 100 Series, medium diffuser kit: P/N 91610146
Exterior Wash 100 Series, wide diffuser kit: P/N 91610147
Exterior Wash 100 Series, very wide diffuser kit: P/N 91610148
Exterior Wash 100 Series, asymmetric diffuser kit: P/N 91610149
Exterior Wash 100 Series, glare shield / snoot: P/N 91611740

Related Items
Martin USB interface box incl. cables: P/N 90758090
M-PC 2U™ incl. Martin M-DMX Interface Box and USB cable: P/N 90737070

Ordering Information
Exterior Wash 110, 10°, EU, aluminum: P/N 90510330
Exterior Wash 110, 10°, US, aluminum: P/N 90513545

