


4

3

2

1

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JBL INCORPORATED. THEY ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR MANUFACTURE OR APPARATUS WITHOUT WRITTEN PERMISSION.


ALL MATERIAL SPECIFIED ON THIS DRAWING SHALL COMPLY WITH EUROPEAN DIRECTIVE 2002/95/EC. 

REVISIONS						
CHG	DATE	DESCRIPTION	DRPT	D/C	DATE	APPR
06882	A	RELEASE TO MARKETING	TP			


**NOTES: (UNLESS OTHERWISE SPECIFIED)**

- COMPONENTS: LF - 2X 2226H 15" DIA. WOOFER  
HF - 1X 2453H 4" DIA. COMPRESSION DRIVER  
1X (90° X 50°) WAVEGUIDE
- INPUT CONNECTORS: 2 NEUTRIK NL4 CONNECTORS
- OPERATING MODE: FULL RANGE/BI-AMP
- GRILLE: 14 GA. PERFORATED CRS, POWDER COATED BLACK WITH BLACK CLOTH BACKING
- MATERIALS: 18MM (.71") 13-PLY BIRCH/POPLAR PLYWOOD
- FINISH: BLACK DURAFLEX
- WEIGHT: 51 Kg (112 LBS).
- SUSPENSION POINTS "•" 12 TOTAL:
  - 3 EA M10 THREAD PATTERN - TOP PANEL
  - 3 EA M10 THREAD PATTERN - BOTTOM PANEL
  - 4 EA M10 THREAD PATTERN - RIGHT/LEFT PANEL
  - 2 EA M10 THREAD PATTERN - REAR PANEL


Δ DIMENSION TAKEN AT FEET




TOP




FRONT



BOTTOM




RIGHT



REAR

**TOLERANCES**  
(UNLESS OTHERWISE SPECIFIED)  
X.XX ± .003 INCH  
X.X ± .125 INCH  
ANGULAR TOLERANCE OF 0°:30'  
FRACTIONAL DIMENSIONS ± 1/32  
\* DIMENSIONS ARE INCHES  
\* ALL DIMENSIONS ARE FINISHED DIMENSIONS  
\* DO NOT SCALE DRAWING

 **JBL PROFESSIONAL**  
A Harman International Company  
Northridge, California 91329 U.S.A.  
**TITLE**  
CUSTOMER DRAWING: STX825  
**SIZE** A **DRAWING NO.** 1000107368 **REV** A  
**SCALE** NTS **SHEET** 1 **OF** 1