

SPECIFICATIONS

PHYSICAL

Length: 330 mm (13.0 in)
Width: 213 mm (8.4 in)
Height: 199 mm (7.8 in)
Weight: 10.4kg (lbs)

SOURCE

Osram HQI-R 150 (included): 150 W, 6000 hr., 4200K

CONTROL

Control options: DMX-512, stand-alone, master/slave
DMX channels: 5
Data I/O: locking 3-pin XLR, pin 1 shield, pin 2 cold (-), pin 3 hot (+)
Recommended cable: ... 24 AWG (min.), low capacitance, 85-150 Ω shielded twisted pair

INSTALLATION

Orientation: horizontal
Minimum distance to combustible materials: 0.1 m (4 in)
Minimum clearance around fan and air vents: 0.1 m (4 in)

AC SUPPLY

Power supply options: 100/120/210/230/250 V, 50/60 Hz (switch-selectable)
Maximum power and current: 205W, 1.9A @ 120V; 195W, 1.0A @ 230V

FUSES

Primary fuse: T 3.15 A, high I²t, 250 V, P/N 05020013
Secondary fuse: T 2.0 A, 250 V, P/N 05020009

CONSTRUCTION

Housing: sheet steel and aluminum
Finish: black, electrostatic powder coating
Protection factor: IP 20

ACCESSORIES

C

Male adaptor for 50 - 300 strand cables with installation materials:	P/N 91611016
G-clamp:	P/N 91602003
Half-coupler clamp:	P/N 91602005
Accessory color filter, blue 111:	P/N 62327015
Accessory color filter, blue 101:	P/N 62327016
Accessory color filter, cyan 401:	P/N 62327017
Accessory color filter, green 202:	P/N 62327018
Accessory color filter, yellow 604:	P/N 62327019
Accessory color filter, red 301:	P/N 62327021
Accessory color filter, pink 312:	P/N 62327022
Accessory color filter, magenta 507:	P/N 62327023
Accessory color filter, purple 502:	P/N 62327025
Accessory color filter, green 204:	P/N 62327034
Accessory color filter, orange 306:	P/N 62327035