

# **MAC Aura™ XB**

## **Acoustic Test Report**



©2017 HARMAN Professional Denmark ApS. Information subject to change without notice. HARMAN Professional and all affiliated companies disclaim liability for any injury, damage, direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document.

Martin®, HARMAN® and all other trademarks in this document pertaining to services or products by HARMAN Professional or its affiliates and subsidiaries are registered as the property of HARMAN Professional Denmark ApS.

HARMAN Professional Denmark ApS - Olof Palmes Allé 18 - 8200 Aarhus N - Denmark - [www.martin.com](http://www.martin.com)

## Title

MAC Aura XB Acoustic Test Report

## Test conditions

Test carried out according to ISO 3744:2010(E)

## Device tested

Make: HARMAN Professional Denmark ApS

Test Date: August 20, 2014

Model: MAC Aura XB

Software version: 1.0.0

## Results

An image of the test setup can be found on page 4. Test results are listed in Table 1 and Table 2 on pages 5 and 6.

HARMAN Professional Denmark ApS, R&D QA are responsible for the test results given in this report.

## Environment

Temperature: 26.1°C Ta

Humidity: 45.3 %RH

AC mains power: 230 V, 50 Hz

Warm-up time: Minimum 20 minutes at full intensity.

Fixture placement: Fixture was placed at least one meter from walls and ceiling, as described in the Standard ISO 3744:2010(E)

## Remarks

Test results apply only to the tested specimen.

Rev: (last five)	Made by:	Description:	Approved by:	Date approved:
A	Dennis Svane	MAC Aura XB Sound Measurement	Markus Klüsener	2017-11-10

## Setup

The product was placed indoors in a hemi-anechoic chamber at the test facility of DELTA in Aarhus, Denmark (see Figure 1). The ceiling and walls were all acoustically absorbent and the floor was reflective. The main dimensions of the room were 12 m x 8 m x 4.5 m (length x width x height).



**Figure 1:** Test setup

The product was allowed a minimum of 20 minutes of warm-up time before measurements were performed.

## Measurement method

Measurements were carried out using a setup with 3 microphones. The microphones were in turn moved to the measurement positions described below.

The following measurement setup was used to determine the sound power level:

Measurement setup:

- Box measurement model
- 9 microphone positions in total
- Measurement surface area: 25.48 m<sup>2</sup>
- Measurement distance: 1 m to a reference box enclosing the test object

## Instrumentation

Please refer to Page 7 for a full instrumentation list.

## Results

The MAC Aura XB was measured in the following state:

- Output intensity = 100%, Mode = Extended color, Fan Mode = Regulated fan

Sound Pressure Levels are listed in Table 1 below. Results of Sound Power Level measurements are listed in Table 2 on Page 6.

Sound Pressure Levels	
Distance from fixture	Scenario 1 [ dB(A) ]
LpA at 0 m	36.9
LpA at 1 m	28.9
LpA at 4 m	16.9
LpA at 7 m	12.0

Sound Pressure Levels have been converted from Sound Power Levels using the formula:  
 $LpA = (LwA - \text{reduction}_{\text{distance}})$

Reductions used: 8 dB(A)@1 m, 20 dB(A)@4 m, 24.9 dB(A)@7 m

**Table 1: Sound Pressure Levels**

The measurement results corrected for background noise are listed in the table below for 1/1-octave band and A-weighted values. Results marked with an (\*) do not meet the 6 dB criterion in clause 4.2.1.1 of ISO 3744:2010(E) for the difference between measured sound power level and background noise.

**1/1 Octave bands and A-weighted sound power levels**

Measured Sound Power Levels	
1/1 Octave band, Hz	Scenario 1 [ Lw, dB re.1pW ]
63 Hz	19.2*
125 Hz	24.3*
250 Hz	23.0*
500 Hz	27.2*
1000 Hz	31.8*
2000 Hz	28.4*
4000 Hz	30.6*
8000 Hz	26.8*
<b>A-weighted (LwA, dB re.1pW)</b>	<b>36.9</b>

*These results are corrected for background noise with a maximum of 2 dB only.*

*Results marked with a (\*) do not meet the 6 dB criterion in clause 4.2.1.1 in ISO 3744:2010(E) for the difference between measured sound pressure level and background noise.*

**Table 2: Measured Sound Power Levels**

## Instrumentation

No.	Equipment	Make	Type
02L021	Calibrator	Brüel & Kjær	4231
14L002	Data acquisition card	National Instruments	NI9233
06L061	½" Microphone	G.R.A.S	40AE
06L064	½" Microphone	G.R.A.S	40AE
06L067	½" Microphone	G.R.A.S	40AE
09L037	Preamplifier	G.R.A.S	26CF
09L038	Preamplifier	G.R.A.S	26CF
09L044	Preamplifier	G.R.A.S	26CF

**Table 3: Instruments Used**

The programs *noiseLAB Capture Professional version 3.0.17* and *Batch processor version 3.1.0* were used for recording and analysis. All instruments and programs are calibrated regularly in accordance with DANAK guidelines.

