



Extension cables to be used between P3 PowerPort and VC-Feeder, or between a VC-Feeder and the next VC-Feeder in the chain.

CONSTRUCTION Power Conductors (2): AWG14 (black & white)
 Data Conductors (2): AWG22 (green & red)
 Shielding: Around data conductor pair + drain wire AWG24
 Jacket: Environmental Protection PVC 65P (RoHS Compliant and UV Resistant)
 Cable Diameter: 7.3 mm (0.29 in)
 Connector Diameter: 20.0 mm (0.79 in)
 Color: Matt black
 Protection Rating: IP65
 RoHS Compliant

WEIGHT 0,103kg / m

CONNECTORS 6-pin custom IP65-rated

APPROVALS UL2517

RELATED ITEMS VC-Feeder™ P/N 90357040

ORDERING INFORMATION

Hybrid Extension Cable, IP65 to IP65, 1 m (3.3 ft.)	P/N 11840167
Hybrid Extension Cable, IP65 to IP65, 2.5 m (8.2 ft.)	P/N 11840168
Hybrid Extension Cable, IP65 to IP65, 5 m (16.4 ft.)	P/N 11840169
Hybrid Extension Cable, IP65 to IP65, 10 m (32.8 ft.)	P/N 11840170
Hybrid Extension Cable, IP65 to IP65, 25 m (82.0 ft.)	P/N 11840164

Hybrid Extension Cable IP65

