


GENERIC SYSTEM DIAGRAM – VC-DOT 1 WITH P3 CONTROL (PowerPort 1500)

P3 Controllers




P3-PC™
P/N 90721030

- Up to 20,736 pixels
- On-screen grabber for video-capture
- Maximum 500 VC-Dot strings



- Up to 100,000 pixels
- Supports input resolutions up to full HD (1920x1080)
- Maximum 500 VC-Dot strings
- DVI Video input



- Up to 520,000 pixels
- Supports input resolutions up to full HD (1920x1080)
- Maximum 500 VC-Dot strings
- DVI Video input




- Up to 2,080,000 pixels
- Supports input resolutions up to full HD (1920x1080)
- Maximum 500 VC-Dot strings
- DVI or 3G-SDI Video input

Maximum 100m Ethernet Cable between any 2 devices (extendable via Gigabit Switch or conversion to fiber)

CAT5E STP CABLES (PROVIDED BY OTHERS)

VC-Dot 1 generic layout



4-pin XLR-BBD Adaptor
P/N 91616046

Hybrid Power+Data Cable CMX BBD-BBD
P/N 91616055 (1m)
P/N 91616056 (2,5m)
P/N 91616057 (5m)
P/N 91616058 (10m)
P/N 91616059 (25m)
P/N 91616060 (100m raw cable)
P/N 91611750 (BBD Male Connector)
P/N 91611751 (BBD Female Connector)

Low Smoke Zero Halogen (LSZH) version:
P/N 91616012 (1m)
P/N 91616013 (2,5m)
P/N 91616014 (5m)
P/N 91616015 (10m)
P/N 91616016 (25m)
P/N 91616017 (100m raw cable)

Up to 4 daisy-chains per Powerport
(one per output)

Maximum VC-Dot 1 per PowerPort
Up to 1200 VC-Dot 1's per P3 PowerPort

Maximum VC-Dot 1 per output
Up to 300 VC-Dot 1's per daisy-chain

Examples:
3 strings of 100 VC-Dot 4's or
4 strings of 75 VC-Dot 4's or
5 strings of 60 VC-Dot 4's or ...

Total length from PowerPort to last VC-Feeder should be less than **50m** (not including the VC-Dot string itself)

VC-Feeder™
with BBD Connector
P/N 90357041

VC-Dot 1™
P/N 90357060

Standard VC-Dot 1 configuration:
LED color: RGB
Pitch: 100 mm (4.0 in.)
No. of Dots: 100 pcs.
Lead-in: 2 m (6.6 ft.)

Hybrid Power+Data Cable CMX BBD-BBD
(Not required if VC-Feeders are mounted next to each other (<20cm))

VC-Feeder™
with BBD Connector
P/N 90357041

VC-Dot 1™

Hybrid Power+Data Cable CMX BBD-BBD
(Not needed if VC-Feeders are mounted next to each other (<20cm))

2m Lead-in Cable		5m Lead-in Cable (max)	
Dot Spacing [mm]	Max. Number Of Dots per String/ VC-Feeder [Pcs]	Dot Spacing [mm]	Max. Number Of Dots per String/ VC-Feeder [Pcs]
100	100 Std. Ver.	100	100
200	100	200	100
300	100	300	100
400	100	400	100
500	100	500	100
600	100	600	100
700	100	700	100
800	100	800	96
900	95	900	91
1000	90	1000	87

Configuration limitations:

Maximum number of pixels per string:	100 Pcs.
Standard pixel spacing (pitch):	100 mm (4.0 in.)
Minimum pixel spacing (pitch):	100 mm (4.0 in.)
Maximum pixel spacing (pitch):	1000 mm (39.4 in.)
Standard lead-in cable length:	2000 mm (78.8 in.)
Maximum lead-in cable length:	5000 mm (196.9 in.)

One pixel = one Dot

Please contact your local sales person for customized VC-Dot strings.


GENERIC SYSTEM DIAGRAM – VC-DOT 1 WITH P3 CONTROL (PowerPort 1000 IP65)

P3 Controllers




P3-PC™
P/N 90721030

- Up to 20,736 pixels
- On-screen grabber for video-capture
- Maximum 500 VC-Dot strings



Martin P3-050 Controller™
Video signal processor
P/N 90721090

- Up to 100,000 pixels
- Supports input resolutions up to full HD (1920x1080)
- Maximum 500 VC-Dot strings
- DVI Video input



Martin P3-150 Controller™
Video signal processor
P/N 90721015

- Up to 520,000 pixels
- Supports input resolutions up to full HD (1920x1080)
- Maximum 500 VC-Dot strings
- DVI Video input




Martin P3-300 Controller™
Video signal processor
P/N 90721060

- Up to 2,080,000 pixels
- Supports input resolutions up to full HD (1920x1080)
- Maximum 500 VC-Dot strings
- DVI or 3G-SDI Video input

Maximum 100m Ethernet Cable between any 2 devices (extendable via Gigabit Switch or conversion to fiber)

CAT5E STP CABLES (PROVIDED BY OTHERS)

VC-Dot 1 generic layout



Martin P3- PowerPort 1000 IP65™
P/N 90721080

To next P3 PowerPort 1000 IP65

Hybrid Power+Data Cable CMX BBD-BBD

- P/N 91616055 (1m)
- P/N 91616056(2,5m)
- P/N 91616057 (5m)
- P/N 91616058 (10m)
- P/N 91616059 (25m)
- P/N 91616060 (100m raw cable)
- P/N 91611750 (BBD Male Connector)
- P/N 91611751 (BBD Female Connector)

Low Smoke Zero Halogen (LSZH) version:

- P/N 91616012 (1m)
- P/N 91616013(2,5m)
- P/N 91616014 (5m)
- P/N 91616015 (10m)
- P/N 91616016 (25m)
- P/N 91616017 (100m raw cable)



VC-Feeder™
with BBD Connector
P/N 90357041

VC-Dot 1™
P/N 90357060

Standard VC-Dot 1 configuration:

- LED color: RGB
- Pitch: 100 mm (4.0 in.)
- No. of Dots: 100 pcs.
- Lead-in: 2 m (6.6 ft.)



Hybrid Power+Data Cable CMX BBD-BBD
(Not required if VC-Feeders are mounted next to each other (<20cm))

VC-Feeder™
with BBD Connector
P/N 90357041

VC-Dot 1™



Hybrid Power+Data Cable CMX BBD-BBD
(Not needed if VC-Feeders are mounted next to each other (<20cm))

Total length from PowerPort to last VC-Feeder should be less than **50m** (not including the VC-Dot string itself)

Up to 4 daisy-chains per Powerport (one per output)

Maximum VC-Dot 1 per PowerPort
Up to 800 VC-Dot 1's per P3 PowerPort

Maximum VC-Dot 1 per output
Up to 200 VC-Dot 1's per daisy-chain

Examples:

- 2 strings of 100 VC-Dot 4's or
- 4 strings of 50 VC-Dot 4's or
- 8 strings of 25 VC-Dot 4's or ...

2m Lead-in Cable		5m Lead-in Cable (max)	
Dot Spacing [mm]	Max. Number Of Dots per String/ VC-Feeder [Pcs]	Dot Spacing [mm]	Max. Number Of Dots per String/ VC-Feeder [Pcs]
100	100 Std. Ver.	100	100
200	100	200	100
300	100	300	100
400	100	400	100
500	100	500	100
600	100	600	100
700	100	700	100
800	100	800	96
900	95	900	91
1000	90	1000	87

Configuration limitations:

Maximum number of pixels per string:	100 Pcs.
Standard pixel spacing (pitch):	100 mm (4.0 in.)
Minimum pixel spacing (pitch):	100 mm (4.0 in.)
Maximum pixel spacing (pitch):	1000 mm (39.4 in.)
Standard lead-in cable length:	2000 mm (78.8 in.)
Maximum lead-in cable length:	5000 mm (196.9 in.)

One pixel = one Dot

Please contact your local sales person for customized VC-Dot strings.

DMX Source

GENERIC SYSTEM DIAGRAM – VC-DOT 1 WITH DMX CONTROL




(PROVIDED BY OTHERS)

DMX limitations with Pixel-level control (1 universe)

VC-Dot 1: 170 dots

VC-Dot 1 generic layout



2m Lead-in Cable		5m Lead-in Cable (max)	
Dot Spacing [mm]	Max. Number Of Dots per String/ VC-Feeder [Pcs]	Dot Spacing [mm]	Max. Number Of Dots per String/ VC-Feeder [Pcs]
100	100 Std. Ver.	100	100
200	100	200	100
300	100	300	100
400	100	400	100
500	100	500	100
600	100	600	100
700	100	700	100
800	100	800	96
900	95	900	91
1000	90	1000	87

Configuration limitations:

Maximum number of pixels per string:	100 Pcs.
Standard pixel spacing (pitch):	100 mm (4.0 in.)
Minimum pixel spacing (pitch):	100 mm (4.0 in.)
Maximum pixel spacing (pitch):	1000 mm (39.4 in.)
Standard lead-in cable length:	2000 mm (78.8 in.)
Maximum lead-in cable length:	5000 mm (196.9 in.)

One pixel = one Dot

Please contact your local sales person for customized VC-Dot strings.

CABLES:
D - DMX CABLE F - FIBER OPTIC CABLE (PROVIDED BY OTHERS) H - HYBRID CABLE (PROVIDED BY MARTIN) P - POWER CABLE V - DVI VIDEO (PROVIDED BY OTHERS) N - CAT6 STP CABLE (PROVIDED BY OTHERS)

Information subject to change without notice. HARMAN Professional Denmark ApS disclaims liability for any injury, damage, direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document. Rev A – 22-10-2018