

EXTERIOR WASH 120

FULLY WEATHERIZED DYNAMIC COLOR TEMPERATURE WASH LIGHT

SPEC SHEET



HIGHLIGHTS

- Variable color temperature control with 6 beam angle options
- Functional and discreet optional snoot which integrates with the design of the fixtures
- Control via DMX, RDM and OLED display

OVERVIEW

Exterior™ Wash 120 is a powerful, compact and energy-efficient LED lighting fixture designed to illuminate smaller structures, features of a building and landscaping. A discreet, optional snoot integrates seamlessly with the slick design of the fixtures. It has built-in display for ease-of-use, a wide selection of beam angles and is fully IP-rated for permanent outdoor use.

The Exterior Wash 120 is designed for variable color temperature (2700K-6500K) applications and is based on separate 2700K and 6500K LEDs

KEY MESSAGES

BUILT TO LAST

Ideal for minimal maintenance, low total cost of ownership, and resiliency to weather and other environmental conditions. Operates at temperatures from -30°C to 45°C and its robust, vandalism-proof IK08 and fully convection cooled IP66-rated aluminum housing is surface-treated to comply with the ISO12944/C5-M corrosion marine protection standard.

EASY TO INSTALL

The Exterior Wash comes pre-installed with power and data cable has integrated multirange 100-277V power supply, so no external control boxes are required.

FLEXIBLE BEAM CONTROL

The warm and cool color LEDs allows for precise color temperature control from 2700 K to 6500 K. Optional beam angle is installed via externally mounted holographic prismatic diffuser lens, ensuring precise beam control and very high transmission rate.

EASY TO CONTROL

The Exterior Wash features RDM and DMX control for great integration in control systems. The built-in OLED display allows for easy configuration and on-board stand-alone programming with up to 20 scenes.

EXTERIOR WASH 120

FULLY WEATHERIZED DYNAMIC COLOR TEMPERATURE WASH LIGHT

SPEC SHEET

FEATURES

- Powerful LEDs (2700K, 6500K)
- Up to 2400 lumens at full white
- Six different beam angle options
- Internal power and control (DMX, RDM and OLED display)
- Rugged IP66 housing
- 0–100% intensity control

ORDERING INFORMATION

- Exterior Wash 120, 7°, EU, aluminum: P/N 90510335
- Exterior Wash 120, 7°, US, aluminum: P/N 90510350

INCLUDED ITEMS

- Cover plate for control panel

RELATED ITEMS

- Martin Companion Cable: P/N 91616091

ACCESSORIES

- Exterior Wash 100 Series, narrow diffuser kit: P/N 91610145
- Exterior Wash 100 Series, medium diffuser kit: P/N 91610146
- Exterior Wash 100 Series, wide diffuser kit: P/N 91610147
- Exterior Wash 100 Series, very wide diffuser kit: P/N 91610148
- Exterior Wash 100 Series, asymmetric diffuser kit: P/N 91610149
- Exterior Wash 100 Series, glare shield / snoot: P/N 91611740
- Exterior Wash 100 honeycomb louvre: P/N 91611856



EXTERIOR WASH 120

FULLY WEATHERIZED DYNAMIC COLOR TEMPERATURE WASH LIGHT

SPEC SHEET

TECHNICAL SPECIFICATIONS

DYNAMIC EFFECTS

Intensity 0 - 100%
Color temperature control 2700 K - 6500 K

CONTROL AND PROGRAMMING

Control systems DMX, RDM
DMX channels 3
Setting, addressing, standalone programming Control panel with OLED display
Receiver RS-485
Firmware update Serial upload via DMX link
DMX compliance USITT DMX512-A
RDM compliance ANSI/ESTA E1.20

OPTICS

Minimum LED lifetime 50 000 hours (to >70% luminous output)*
Light source Light source: 2700 K and 6500 K LEDs
LED manufacturer Cree

*Figure obtained under manufacturer's test conditions

PHOTOMETRIC DATA

Beam angle	Total output	Center peak
No diffuser: 7.5°	2 400 lumens	118 000 cd
Narrow diffuser: 11.5°	2 200 lumens	48 000 cd
Medium diffuser: 22°	2 300 lumens	13 000 cd
Wide diffuser: 50°	2 400 lumens	3 400 cd
Very wide diffuser: 60°	2 400 lumens	2 500 cd
Asymmetric diffuser: 61° x 15°	2 300 lumens	7 600 cd

CONSTRUCTION

Ingress protection rating IP66
Surface treatment Anodized and electrostatic powder-coated
Color Light grey (white, black or other colors available on request)
Housing Cast aluminum
Effective Projected Area (EPA) 0.05 m² including snoot
Impact resistance IK08 (with display panel cover plate installed)
Corrosion resistance C5-M (very high corrosivity / marine, ISO 12944)
RoHS compliant

INSTALLATION

Orientation Any
Mounting Adjustable yoke
Minimum distance to illuminated surfaces 0.2 m (0.6 ft.)

CONNECTIONS

Power connection 1.8 m (5.9 ft.) cable tail without connector
Power input cable type, EU models H05RN-F 300/500V, 3 x 0.75 mm², Ø 7 mm
Power input cable type, US models SJOW 18AWG, 300V, WL F1, Ø 8 mm
Data connection 1.8 m (5.9 ft.) open ended 5-conductor combined input + output cable tail
All cable entries IP68 cable gland

ELECTRICAL

AC power 100 - 240 / 277 V nominal, 50/60 Hz
Power supply unit Integrated, auto-sensing multi-voltage
Power consumption steady state, all LEDs at zero intensity 5 W
Maximum total power consumption 50 W
Typical half-cycle RMS inrush current 9.7 A
Surge protection 4 KV

TYPICAL POWER AND CURRENT

100 V, 60 Hz 0.45 A, 42 W, PF 0.99
120 V, 60 Hz 0.36 A, 43 W, PF 0.99
230 V, 50 Hz 0.2 A, 43 W, PF 0.97
277 V, 60 Hz 0.2 A, 43 W, PF 0.90

Measurements made with fixture in steady state at nominal voltage, ambient temperature (Ta) 20° C (68° F), all LEDs at full intensity. Allow for a deviation of +/- 10%.

THERMAL

Cooling Convection
Maximum ambient temperature (Ta max.) 45° C (113° F)*
Minimum ambient temperature (Ta min.) -30° C (-22° F)**
Maximum surface temperature, steady state, at 40° C ambient 70° C (158° F)
Total heat dissipation (calculated, +/- 10%) 160 BTU/hr

*Above this temperature, the fixture regulates output to protect from overheating.

**To ensure correct low temperature start-up, power must be maintained below -20° C (-4° F)

APPROVALS

EU safety EN60598-2-5 (EN60598-1), EN62471, EN62493, EN60598-2-1
EU EMC EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN61000-4-2, EN61000-4-4, EN61000-4-5
US safety ANSI/UL 1598
US EMC 47 CFR Part 15 Class A
Canadian safety CSA C.22.2 No. 250
Australia/NZ RCM



EXTERIOR WASH 120

FULLY WEATHERIZED DYNAMIC COLOR TEMPERATURE WASH LIGHT

SPEC SHEET

PROJECTION DATA

NO DIFFUSER (7.5°)

Distance in meters (ft.)	2 m (6.6 ft.)	4 m (13.1 ft.)	6 m (19.7 ft.)	8 m (26.2 ft.)	10 m (32.8 ft.)	12 m (39 ft.)	14 m (46 ft.)	16 m (52 ft.)	18 m (59 ft.)
Half-peak diameter in meters (ft.)	0.3 (0.9)	0.5 (1.7)	0.8 (2.6)	1.0 (3.4)	1.3 (4.3)	1.6 (5.2)	1.8 (6.0)	2.1 (6.9)	2.4 (7.7)
Center illuminance in lux	29500	7375	3278	1844	1180	819	602	461	364
Center illuminance in candela	2741	685	305	171	110	76	56	43	34

NARROW DIFFUSER (11.5°)

Distance in meters (ft.)	2 m (7 ft.)	4 m (13 ft.)	6 m (20 ft.)	8 m (26 ft.)	10 m (33 ft.)	12 m (39 ft.)	14 m (46 ft.)	16 m (52 ft.)	18 m (59 ft.)
Half-peak diameter in meters (ft.)	0.4 (1.3)	0.8 (2.6)	1.2 (4.0)	1.6 (5.3)	2.0 (6.6)	2.4 (7.9)	2.8 (9.3)	3.2 (10.6)	3.6 (11.9)
Center illuminance in lux	12000	3000	1333	750	480	333	245	188	148
Center illuminance in candela	1115	279	124	70	45	31	23	17	14

MEDIUM DIFFUSER (22°)

Distance in meters (ft.)	2 m (7 ft.)	4 m (13 ft.)	6 m (20 ft.)	8 m (26 ft.)	10 m (33 ft.)	12 m (39 ft.)	14 m (46 ft.)	16 m (52 ft.)	18 m (59 ft.)
Half-peak diameter in meters (ft.)	0.8 (2.6)	1.6 (5.1)	2.3 (7.7)	3.1 (10.2)	3.9 (12.8)	4.7 (15.3)	5.4 (17.9)	6.2 (20.4)	7.0 (23.0)
Center illuminance in lux	3250	813	361	203	130	90	66	51	40
Center illuminance in candela	302	75	34	19	12	8	6	5	4

WIDE DIFFUSER (50°)

Distance in meters (ft.)	2 m (7 ft.)	4 m (13 ft.)	6 m (20 ft.)	8 m (26 ft.)	10 m (33 ft.)	12 m (39 ft.)	14 m (46 ft.)	16 m (52 ft.)	18 m (59 ft.)
Half-peak diameter in meters (ft.)	1.9 (6.1)	3.7 (12.2)	5.6 (18.4)	7.5 (24.5)	9.3 (30.6)	11.2 (36.7)	13.1 (42.8)	14.9 (49.0)	16.8 (55.1)
Center illuminance in lux	850	213	94	53	34	24	17	13	10
Center illuminance in candela	79	20	9	5	3	2	2	1	1

VERY WIDE DIFFUSER (60°)

Distance in meters (ft.)	2 m (7 ft.)	4 m (13 ft.)	6 m (20 ft.)	8 m (26 ft.)	10 m (33 ft.)	12 m (39 ft.)	14 m (46 ft.)	16 m (52 ft.)	18 m (59 ft.)
Half-peak diameter in meters (ft.)	2.3 (7.6)	4.6 (15.2)	6.9 (22.7)	9.2 (30.3)	11.5 (37.9)	13.9 (45.5)	16.2 (53.0)	18.5 (60.6)	20.8 (55.1)
Center illuminance in lux	625	156	69	39	25	17	13	10	8
Center illuminance in candela	58	15	6	4	2	2	1	1	1

ASYMMETRIC DIFFUSER (61° x 15°)

Distance in meters (ft.)	2 m (7 ft.)	4 m (13 ft.)	6 m (20 ft.)	8 m (26 ft.)	10 m (33 ft.)	12 m (39 ft.)	14 m (46 ft.)	16 m (52 ft.)	18 m (59 ft.)
Half-peak diameter C ₀ in meters (ft.)	2.4 (7.7)	4.7 (15.5)	7.1 (23.2)	9.4 (30.9)	11.8 (38.7)	14.1 (46.4)	16.5 (54.1)	18.8 (61.8)	21.2 (69.6)
Half-peak diameter C ₉₀ in meters (ft.)	0.5 (2.0)	1.1 (4.1)	1.6 (6.1)	2.1 (8.1)	2.6 (10.2)	3.2 (12.2)	3.7 (14.2)	4.2 (16.3)	4.7 (18.3)
Center illuminance in lux	1900	475	211	119	76	53	39	30	8
Center illuminance in candela	177	44	20	11	7	5	4	3	2

EXTERIOR WASH 120

FULLY WEATHERIZED DYNAMIC COLOR TEMPERATURE WASH LIGHT

SPEC SHEET

DIMENSIONS

PHYSICAL

Length..... 240 mm (9.5 in.)
Width..... 198 mm (7.8 in.)
Height..... 257 mm (10.2 in.)
Weight..... 5.0 kg (11.1 lbs.)

