BSS Soundweb London Reference Chart - 2023

CHASSIS	CUSTOM I/O (CARD-BASED)	ANALOG INPUTS	DIGITAL INPUTS	AEC INPUTS	ANALOG OUTPUTS	DIGITAL OUTPUTS	TELEPHONE CONNECTION	VoIP CONNECTION	CONFIGURED VIA	LCD DISPLAY	LOGIC PROCESSING	ETHERNET	RS-232	GPIO	SIGNAL PROCESSING (MHz)	DANTE / AES67	BLU-LINK DIGITAL AUDIO BUS	
BLU-806DA	19"	✓	≤ 16 *	≤ 16 *	≤ 16 *	≤ 16 *	≤ 16 *	≤ 4 *		SOFTWARE	✓	✓	✓	✓	12 X 6	800	✓	256 ch.
BLU-326DA	19"	✓	≤ 16 *	≤ 16 *	≤ 16 *	≤ 16 *	≤ 16 *	≤ 4 *		SOFTWARE	✓	✓	✓	✓	12 X 6		✓	256 ch.
BLU-160	19"	✓	≤ 16 *	≤ 16 *	≤ 16 *	≤ 16 *	≤ 16 *	≤ 4 *		SOFTWARE	✓	✓	✓	✓	12 X 6	800		256 ch.
BLU-120	19"	✓	≤ 16 *	≤ 16 *	≤ 16 *	≤ 16 *	≤ 16 *	≤ 4 *		SOFTWARE	✓	✓	✓	✓	12 X 6			256 ch.
BLU-103	19"				8	8			1 (2 LINES)	SOFTWARE		✓	✓	✓	12 X 6	400		48 ch.
BLU-102	19"		10		8	8		1		SOFTWARE		✓	✓	✓	12 X 6	400		48 ch.
BLU-101	19"				12	8				SOFTWARE		✓	✓	✓	12 X 6	400		48 ch.
BLU-100	19"		12			8				SOFTWARE		✓	✓	✓	12 X 6	400		48 ch.
BLU-50	HALF-RACK		4			4				SOFTWARE		✓	✓	✓	12 X 6	400		48 ch.
BLU-BIB	HALF-RACK		8							DIP SWITCH								256 ch.
BLU-BOB1	HALF-RACK					8				DIP SWITCH								256 ch.
BLU-BOB2	19"					8				DIP SWITCH								256 ch.
BLU-GPX	19"									SOFTWARE	✓	✓	✓	✓	36 X 23 8 Relays			
BLU-DA	HALF-RACK									SOFTWARE		✓	✓	✓			✓	256 ch.

***16 total inputs/outputs (4 cards) allowed per device**