
Product verification and reliability report

Product: Exterior Projection Pro Compact

Date: 2025-03-24



Test performed	Condition	Duration	Test lab	Result
IK Class Test -Verification of protection against external mechanical impacts 	EN62262, IK-08	N/A	LCS Testing	Pass
Application Vibration Test -Verification of protection against transportation and installation vibration 	1) IEC60068-2-6, Sinusoidal vibration. 3 directions. 2) IEC60068-2-64, Random vibration. ½ hours. 3 directions 3) ANSI C136-31 ((Bridge & Overpass Applications) Fixture powered during test.	3 x 30 mins @resonance frequence (or 30Hz) 3 x 30 mins. 100,000 cycles @resonance frequence (or 30Hz)	Martin Professional	Pass

The material contained in this document supersedes all previous documentation issued for the related products included herein. The document and the information contained, in whole or in part, are protected by copyright laws, trademark and design rights. Any unauthorized use of the document and its contents will be considered a violation of Martin Professional ApS intellectual property rights

Wind load Test - Wind load simulation 	Tested according to EN60598-2-5, 5.6.5 Static load simulating 60 m/sec. (216 km/h) wind force without causing failure or permanent set to mount bracket	10 mins.	Martin Professional	Pass
Thermal Test - -30 °C to +50 °C during operation 	Designed and tested to ambient temperature Ta (min/max): -30 °C to +50 °C	N/A	Martin Professional	Pass
IP Class Test - Verification of protection against intrusion of dust and water 	IP66 according to IEC/EN60529	N/A	NTEK	Pass

The material contained in this document supersedes all previous documentation issued for the related products included herein. The document and the information contained, in whole or in part, are protected by copyright laws, trademark and design rights. Any unauthorized use of the document and its contents will be considered a violation of Martin Professional ApS intellectual property rights

Salt Mist Test - corrosion resistance of materials and surface coatings 	Neutral Salt Spray test, 5%, 35°C, ASTM B117/ ISO 9227, EN 12944-6, C5-H	1440 hours	Martin Professional	
Solar Radiation and Moist Test – Method for exposing fixture or components to UV light in the presence of moisture to reproduce the weathering effects (temperature, humidity and/or wetting) 	ISO 4892-2, cyclic no. 1, 102 mins. dry, 18 mins. water spray.	2500 hours	Martin Professional	Pass

The material contained in this document supersedes all previous documentation issued for the related products included herein. The document and the information contained, in whole or in part, are protected by copyright laws, trademark and design rights. Any unauthorized use of the document and its contents will be considered a violation of Martin Professional ApS intellectual property rights

Surge / Transient Test -Surge immunity from power switches and lightning. 	EN61000-4-5 / Class 4, 4kV	N/A	Guangzhou Quality Supervision and Testing Institute	Pass
Packing Test - Verification of products and packing strength 	ISTA-6A FedEx - International Shipment	N/A	NTEK	Pass
Product Lifetime testing (after 6000h) - Verification of product lifetime in the outdoor environment 	Indoor: All effects running, Ta +30° C Outdoor: All effects running, Ta +5° to +40° depending on season.	21h/day	Martin Professional	Long-term test

Report prepared and verified by:	Kevin, Guo
Department:	Martin Professional, R&D Engineering Test & Validation
Date:	2025-03-24
Revision:	1.2

The material contained in this document supersedes all previous documentation issued for the related products included herein. The document and the information contained, in whole or in part, are protected by copyright laws, trademark and design rights. Any unauthorized use of the document and its contents will be considered a violation of Martin Professional ApS intellectual property rights